

MFS□-P□13 Series

Individual Wiring Type Manifold
Bar Type

MFS□-PS13

Common SUP, captured EXH,
port 1, 3 & 5 on both sides



PC/RC5, 13

Manifold Specifications

		MFS□-PS13
Type of manifold		Common SUP, captured EXH, port 1, 3 & 5 on both sides
Port size	Port 1	Rc¼ (Both side)
	Port 3, 5	Rc¼ (Both side)
	Port 2, 4	Rc¼
N: Number of stations		2~10
Mountable solenoid valve		PCL2413 PCS2413 PCD2413 PCD3413 PCE3413 PCO3413
Blank plate		PC13-BP

Manifold

MFS2-PS13-02

Number of stations

2 : 2 stations
⋮
10 : 10 stations

Port size 2&4

02: Rc¼

Mountable solenoid valve series


PS13: Common SUP, captured EXH, port 1,3 & 5 on both sides

Mountable solenoid valve

PCL2413-NB-D24SP

Model No.

PCL2413



Wiring

L : Lead wire
SP: Connector with lead wire

Voltage

D24: DC24V

Special specifications

No mark : Standard

Y : Captured exhaust of pilot

Port size

NB: Without sub-base

Note: A gasket & two mounting screws come with valve.

Dimensions

For dimensions, refer to the following pages.

MFS□-PS13-02 → B45

The manifolds are the same with those shown on the left.

The configuration of solenoid valve PCL2413 and PCS2413 are the same, but the manual override are different.